

FORD RANGER FIRE TRUCK



VEHICLE SUMMARY

The Fast Attack Fire Module has been designed to get the most versatility from a single vehicle. The quick release mechanisms allow for the Fire Module to be interchanged in a matter of minutes. This means the vehicle can be converted from a robust small response fire unit to a standard tray back vehicle at any time. Limiting downtime, increasing the vehicle's functionality and reducing operating costs.



Automated Pump Electric Flow Switch By-Pass to Protect Pump



Protective Roof

Operational Lighting Package

- Work Lights
- Strip Lighting
- S.T.I.R. High Lights

1600L Tool Box



Electric Starter Kit for Davey Pump
Pump Isolation Switch

Hose Reel Electric Re-Wind
Akron Forestry Nozzle
or Trigger Gun

3-Point Access Ladder



Front protection bull bar with side rail and side step*



Multiple storage lockers (1600L)



Work light



Electric starter kit for davey pump
Pump isolation switch

*Optional

Contact RMA Automotive for more information or a quotation.

✉ inquiries@rmagroup.net

🌐 rmaautomotive.net



FORD RANGER FIRE TRUCK



Vehicle Details

Manufacturer	Ford
Model	Ranger Single Cab
Engine	Turbo Diesel 2.2L TDCi
Power (kW/PS)	88/120 @ 3700 rpm
Torque (Nm)	285 @ 1750 - 2300 rpm
Drivetrain	4X4
Transmission	5-speed manual
Fuel tank capacity	80L
Wheel	16" steel wheel
Tire	All terrain

Dimensions of Modified Vehicle (mm)

Length	5710
Width	1860
Height (without Go Light)	1960
Angle of approach (°)	30.1
Angle of departure (°)	31.2
Wheelbase	3220
Track width	1560
Ground clearance	201
Turning circle (m)	12

Weight Table (kg)

Base vehicle unladen kerb weight	1880
Modified vehicle unladen kerb weight	2680
Gross modified vehicle weight	3200

STANDARD Features

Fire module with aluminium tray

Fork lifting points accessible both sides

Quick release locking system

BIC 65mm fast fill

Protective roof

1600L toolbox

Three-point access ladder

Operational lighting package

Tank low level alarm system

Hose reel electric rewind

Trigger gun

Akron forestry nozzle

Vehicle decals

Heavy duty poly tank

400L capacity, light weight & robust design

Ball baffle system ensuring vehicle stability

Fast fill breather & overflow

Tank level LED indication panel

Low level audible alarm system

Optional Features

Front bull bar (no winch offer)

Side rail and side step protection

Light bar system with PA unit

Front mesh protection

Davey pump

Diesel twin impeller 5270YE

Flows to 800 lpm. max head 92 m.

Self priming pump

Scotty through-pump foam proportioning system

Automated pump electric flow switch by-pass to protect pump

Electric start with battery recharge

Pump starter isolation switch

Hannay hose reel

Electric rewind

Hose rollers

Shut off isolation

30m reinforced hose

Trigger gun nozzle or forestry nozzle available

Notes:

The company reserves the right to change the vehicle specifications and features described in this publication at any time.

Vehicle specifications and features may vary in different markets.

Images are for illustrative purposes only and may appear different to the actual vehicle.

Contact RMA Automotive for more information or a quotation.

✉ inquiries@rmagroup.net

🌐 rmaautomotive.net

